Description

Method and circuit arrangement for the protected
transmission of data words

5

The invention relates to a method and a circuit
arrangement for the protected transmission of data
words in line with the coordinate patent claims.

10   Circuit arrangements for data processing essentially
comprise an arithmetic and logic unit, a memory and
also peripheral units and a bus for data interchange
between the arithmetic and logic unit, the memory and
the peripheral units. The operation of the circuit
15   arrangements can be impaired by errors in the hardware
or external sources of interference.

Previous safety concepts for protecting the data
processing within a circuit arrangement have
20   concentrated on protecting just a portion of the
circuit arrangement. By way of example, providing a
cryptographic unit allows data in the memory to be
protected against incorrect use when read without
authorization. In this context, the data to be stored
25   in the memory are encrypted before being stored and are
decrypted again when they are loaded, so that the
memory contains the data only in encrypted form.

Another protection option is the use of
30   error-correcting codes. In this context, a data word
has redundant information added to it which allows
changes in individual bits to be recognized and
corrected. Error-correcting codes can be used both to
protect the data in the memory and during data
35   transmission, for example via the bus. Data
transmission via the bus can also be protected by
encrypting the data during the transfer.

In the measures cited above, the protection for the data is limited to areas of the circuit arrangement outside of the arithmetic and logic unit.

5   As regards new attack scenarios, comprising local or wide-area attacks using light or heat, new safety concepts are changing to no longer preventing errors during data transmission but rather merely recognizing them and initiating a suitable reaction from the
10 circuit arrangement.

It is an object of the invention to provide a simple method for protected data transmission which can be used to check the entire data traffic as far as the
15 arithmetic and logic unit, and also a suitable circuit arrangement.

The object is achieved by the measures specified in the coordinate patent claims.
20

The method for the protected transmission of data words involves provision of a first data word, transformation of the first data word into a sequence comprising at least one second data word by a first transformation
25 rule, transformation of at least one of the second data words into a third data word by a second transformation rule, and checking whether a prescribed relationship exists between the third data word and a comparison data word.
30

The invention also specifies a circuit arrangement for the protected transmission of data words which is suitable for use of the cited method.

35 Fundamental components of a circuit arrangement for the actual data processing are a memory and an arithmetic and logic unit. The memory contains the program code to

data and instructions. A set of possible instructions
from which the data words of the program code are
chosen is usually chosen such that it can be processed
not just by one particular arithmetic and logic unit
5   architecture, but rather can be used in different
circuit arrangements or arithmetic and logic units.

The data words in the program code cannot be processed
by the arithmetic and logic unit directly, since the
10 arithmetic and logic unit has its own instruction set
which is usually optimized for the arithmetic and logic
unit architecture or more frequent demands. This
instruction set in the arithmetic and logic unit
differs from the instruction set in the program data,
15 which is as flexible as possible and needs to cope with
a large number of demands. For this reason, a first
transformation device, which is also called a decoder,
is provided in order to translate the first data words
in the program data into second data words, matched
20 specifically to the arithmetic and logic unit. The
second data words are instruction words for the
arithmetic and logic unit. Each first data word is
translated into a sequence of data words which
comprises one or more second data words. The second
25 data words which are output by the first transformation
device are processed by the arithmetic and logic unit.

The second data words are generated specifically for
the arithmetic and logic unit, which needs to process
30 the second data words. There are arithmetic and logic
units for which a first data word is translated into a
sequence containing just one second data word. There
are arithmetic and logic units for which a first data
word is translated into a sequence containing a
35 plurality of second data words. In this context, it is
naturally conceivable for the resultant sequence for a
few first data words to comprise just one second data

normally simple and flexible arithmetic and logic units.

The advantage of the method is that no action is taken in the actual data processing of the first or second data words. Rather, the second data words are simultaneously used as control information for the first data words which are based on them. A check is carried out to determine whether the first and second data words still fit together after the data transmission. If this is not the case, it can be assumed that there is an error in the data transmission which is possibly caused by an attack.

The first and second data words are tapped off at suitable points in the circuit arrangement. Suitable points are preferably upstream and downstream of the first transformation device, which converts the first data words into the second data words. The second data word is checked, as described below, to determine whether it has a prescribed relationship with a comparison data word.

The decoder may also be of multistage design. It is conceivable for the second data words to be tapped off between the decoder stages. In this case, the first transformation device corresponds to the decoder stages between the taps. It is likewise conceivable for the first transformation device to comprise a plurality of decoders which are connected downstream of one another. Further decoders may be provided upstream and/or downstream of the taps. The first transformation rule then relates to the transformations carried out between the taps. The choice of tap allows a tradeoff between complexity and scope of protection.

For checking purposes, the second data word is

transformation is chosen such that its result matches a comparison data word when no error has arisen during the transmission. The comparison data word is advantageously the first data word. It is also

5 conceivable for the third data word and the comparison data word to have a prescribed relationship. Inversion or shifting are conceivable relationships, as is a match between selected bit positions within the data words. The latter is not a unique relationship between

10 two data words, however. A set of data words may satisfy this relationship. For the error recognition, however, it is advantageous if the relationship is such that a data word has the comparison data word distinctly associated with it.

15

If each first data word is converted during the first transformation into a sequence containing precisely one second data word, the method normally comprises mutually inverse first and second transformations if

20 the comparison data word is the first data word.

If a sequence containing a plurality of second data words is generated from the first data word during the decoding, just one of these second data words

25 frequently cannot be used to obtain a distinct inference regarding which first word is to be attributed the second data word. On account of the simpler structure of the arithmetic and logic unit, the latter's instruction set is frequently smaller than the

30 set of possible first data words. Consequently, the same second data word is part of different sequences which are obtained when various first data words are transformed. A single second data word within the sequence allows no further inference of the underlying

35 first data word. A plurality of first data words may be used. For this reason, the result of the second transformation of a second data word, which is

in the sequence, may comprise a set containing possible first data words, which may include the second data word. Since the distinct relationship between a single second data word and the underlying first data word has

5   already been lost during the first transformation, this relationship also does not exist after the second transformation of the second data word. The first and third data words therefore no longer have a distinct relationship. Rather, there is then a relationship

10 between a third data word and a plurality of first data words.

To improve protection, it is desirable for the result of the second transformation to allow a distinct

15 inference of the first data word, which is associated with the second data word. For this reason, the generated second data words advantageously have additional information added to them revealing that first data word from which the second data word has

20 been transformed. This practice is useful when the second data word is within a sequence containing a plurality of second data words which have been converted from the first data word. Second data words which occur within a plurality of possible sequences

25 can therefore always be associated with the first data word underlying this sequence separately from the sequence. This means that a distinct relationship between the first and third data words can also be ensured after a second transformation.

30

Frequently, the circuit implementation of the second transformation rule as a reverse transformation of the first transformation rule gives rise to difficulties. In this case, the second transformation is in the form

35 of just a partial reversal of the first transformation. The result provided for the second transformation is then not the original first data word but rather a

word with the first data word, the first data word is
likewise transformed. A third transformation used for
this needs to be chosen such that its result matches
the result of the first transformation together with
5 the subsequent partial reversal of this through the
second transformation, or results in the comparison
data word, which has the prescribed relationship with
the third data word.

10 A circuit arrangement based on the method outlined
above comprises further blocks in addition to the
conventional circuit arrangement for data processing.
The first transformation device converts the first data
word into the second data word or into the sequence of
15 second data words. Advantageously, the second data word
is tapped off upstream of the arithmetic and logic unit
and is converted by means of a second transformation
device into the third data word, which can be compared
with the first data word. This is done using a checking
20 device.

If the second transformation device does not permit
full reversal of the first transformation, a third
transformation device needs to be provided between the
25 memory and the checking device, so that the third
transformation device and the string comprising the
first and second transformation devices deliver a
respective data word, which are then able to be checked
to determine whether the prescribed relationship
30 exists.

If the first, possibly transformed, data word and the
third data word do not match, the checking device
executes an alarm function, for example an alarm
35 signal.

Further advantageous refinements of the invention are

The invention is explained below using exemplary embodiments with reference to the drawing, in which:

5   Figure 1 show a first exemplary embodiment of a method for the protected transmission of data words,

Figure 2 shows a further exemplary embodiment of the method for the protected transmission of data words,

10

Figure 3 shows yet a further exemplary embodiment of the method for the protected transmission of data words,

15   Figure 4 shows an exemplary embodiment of a circuit arrangement for the protected transmission of data words, and

Figure 5 shows a further exemplary embodiment of the
20   circuit arrangement for the protected transmission of data words.

Figure 1 shows a simple exemplary embodiment of a method for checking a first data word X1 which is
25   converted into a second data word X2.

First of all, the basic cycle of the inventive method will be illustrated using a simple exemplary embodiment. A first transformation T1 is used to
30   generate a sequence S2 of data words from a first data word X1. In the case illustrated, the sequence S2 comprises precisely one second data word X2.

The second data word X2 is converted into a third data
35   word X3 by means of a second transformation T2. In this case, a prescribed relationship exists between the third data word X3 and the first data word X1. Ideally,

word X3 is identical to the first data word X1. This is the case when the second transformation T2 is a reverse transformation of the first transformation T1.

5   A check K is used to check whether a prescribed relationship exists between the third data word X3 and a comparison data word VX. In this case, the comparison data word VX is the first data word X1. If the second transformation T2 is the reverse function of the first
10   transformation T1, this involves a check for identity between the first data word X1 and the third data word X3. If the third data word X3 and the first data word X1 do not have the prescribed relationship, or these data words are not identical, an alarm function ALARM
15   is performed.

The alarm function ALARM may be in many different forms and is also dependent on the use of the method. Details in this regard can be found in the description of the
20   circuit arrangement.

Figure 2 shows a further exemplary embodiment of the method for the protected transmission of data words. In this case, the first data word X1 is transformed into a
25   sequence S2 comprising a plurality of second data words X2 by the first transformation T1.

In these cases, it is no longer necessarily possible to associate with each individual one of the second data
30   words X2 in the sequence S2 distinctly with the first data word X1. Since the set of possible data words which is intended for the arithmetic and logic unit is smaller, the same second data words X2 are converted into different possible sequences S2 which are
35   respectively associated with a first data word X1. This means that a single data word X2 is no longer distinctly associated with the first data word X1, but

data words X2 as a whole.

Depending on the first data word X1, the number of
second data words X2 in the relevant sequence S2 may
5   vary. It is also conceivable for the sequence S2 to
comprise just a single second data word X2.

The second transformation T2 is used to convert each of
the second data words X2 into a third data word X3.
10   There is no guarantee that the first data word X1 can
be inferred from an individual, second data word X2
within the sequence S2. This means that after the
second transformation T2 the first and one of the third
data words X3 are not necessarily in a distinct
15   relationship. It is not necessarily possible to infer
the underlying first data word X1 from a third data
word X3. However, it is possible, by way of example, to
infer a set of possible first data words X1 from the
third data word X3. In this case, the error recognition
20   is restricted. The check K then checks whether the
original first data word X1 is contained in the set of
possible first data words which is obtained after the
second transformation T2. If this is not the case, it
is possible to infer an error. If the set of possible
25   first data words does comprise the original first data
word X1, on the other hand, two possibilities are
conceivable. The transmission was error-free or, if the
transmission produced an error, this error resulted in
a set of possible first data words which likewise
30   comprises the original first data word X1.

An example is intended to illustrate the problem. It is
assumed that the program code contains an instruction
"ADD-SHIFT" as first data word X1. "ADD-SHIFT" adds two
35   register addresses and shifts the resultant address by
one bit. In addition, an instruction "ADD-LOAD" is
assumed to be provided as a further first data word X1,

the resultant address being passed to the system in order to load a data item from this address. The first transformation T1 converts the instruction "ADD-SHIFT" into a sequence S2 containing an "ADD" instruction and

5   a "SHIFT" instruction as second data words X2. The instruction "ADD-LOAD" is converted into a sequence S2 containing an "ADD" instruction and a "LOAD" instruction as second data words X2. In both sequences S2, the "ADD" instruction appears first of all as the

10   first of the second data words X2. If just this second data word X2 in the two sequences S2 is considered, it is not possible to distinguish whether the underlying first data word X1 is the instruction "ADD-SHIFT" or "ADD-LOAD". The first data word X1 can be inferred only

15   from "ADD". The second data word X2 can originate either from the first data word "ADD-SHIFT" or from the first data word "ADD-LOAD". In this example, an error can be inferred from "ADD" only if the first data word X1 is neither "ADD-SHIFT" nor "ADD-LOAD".

20

To increase the safety of the method, each second data word X2 is attributed information I after the first transformation T1, so that the resultant second data word X2 can be distinctly associated with the first

25   data word X1.

In the example above, by way of example, the second data word X2 "ADD" has a bit, "0" or "1", added to it from which it is possible to tell whether the first

30   data word X1 is an "ADD-SHIFT" instruction or an "ADD-LOAD" instruction. By way of example, an "ADD0" is transformed into an "ADD-SHIFT", and an "ADD1" is transformed into an "ADD-LOAD". Each of the third data words X3 is thus distinctly in a prescribed

35   relationship with the underlying first data word X1. This means that it is also possible to use the second transformation T2 to output a third data word X3 which

X1. The check K checks the prescribed relationship. If the relationship does not exist, an alarm function ALARM is performed.

5   Advantageously, the third data words X3 are identical to the first data word X1. Since identical third data words X3 are generated from a first data word X1 using different second data words X2, the second transformation T2 is not a unique depiction. In this

10   exemplary embodiment too, the first data word X1 is the comparison data word VX.

For safety reasons, each second data word X2 in the sequence S2 should be converted into a respective third

15   data word X3, which are compared with the relevant comparison data word VX, in this case the first data word X1. Alternatively, it is conceivable to subject just a portion of the second data words X2 to the second transformation T2 and to check them.

20

Figure 3 shows a further refinement of the method. It differs from the method shown in Figure 2 by means of a third transformation in the path between the first data word X1 and the check K. For this reason, only the

25   differences are discussed below.

In this exemplary embodiment, the second transformation T2 is chosen such that it is not a reverse transformation of the first transformation T1. In this

30   case, the third data words X3 do not match the first data word X1. To be able to perform a check K for identity nevertheless, the first data word X1 is subjected to a third transformation T3. The third transformation T3 is chosen such that it delivers the

35   same result as the string comprising the first and second transformations T1, T2.

transformations T1, T2, T3 can be chosen such that the
second transformation T2 is identity, i.e. the input
and the output of the transformation are the same. This
would be equivalent to omitting the circle T2 in Figure

5   3. In this case, the first and third transformations
T1, T3 are the same depiction when the check K for
identity is performed.

Figure 4 shows a circuit arrangement in which the

10 method described is used. The circuit arrangement
comprises a memory MEM and an arithmetic and logic unit
CPU. It will be noted that the memory MEM may also be a
buffer store which is connected downstream of an actual
main memory.

15

To match the first data words X1 provided for data
processing in the memory MEM, a first transformation
device DEC is provided which matches the first data
words X1 in a program code to the instruction set in

20 the arithmetic and logic unit CPU. This corresponds to
the first transformation T1 outlined above. The
architecture of the arithmetic and logic unit and of
the first transformation device DEC may, as one
alternative, be chosen such that it is a "RISC"

25 architecture, in which each first data word X1 is
attributed a sequence S2 containing precisely one
second data word X2. It may also be a CISC
architecture, in which the first data word X1 is
converted into a sequence S2 comprising a plurality of

30 second data words X2. The number of second data words
X2 in the sequence S2 may vary. A sequence S2
containing just one second data word X2 is also
conceivable in this context.

35 The data are loaded from the memory MEM via a plurality
of buffer stages. Figure 4 shows a first buffer stage 1
and a second buffer stage 2, by way of example, which

transformation device DEC. The first buffer device 1 provides the first data words X1 for the first transformation device DEC. From the second buffer stage 2, the second data words X2 are provided for the

5   downstream arithmetic and logic unit CPU for the actual processing. Along the path described, the actual data processing of the data words takes place from the memory MEM to the arithmetic and logic unit CPU. It would also be conceivable to tap off the first and

10 second data words X1, X2 directly upstream and downstream of the first transformation device DEC. The taps can also be made directly downstream of the memory MEM and/or upstream of or even by the arithmetic and logic unit CPU. The protected area is dependent on the

15 choice of taps along the data transmission path.

To verify whether the second data word X2 provided for the arithmetic and logic unit CPU is correct in the second buffer device 2, or has been manipulated on the

20 way there, a second transformation device R1 and a checking device COMP are provided. The checking device COMP is coupled both to the second buffer 2 via the second transformation device R1 and to the first buffer 1. The second transformation device R1 is designed to

25 convert the second data word X2 into the third data word X3.

The checking device COMP is designed to check an applied data word and an applied comparison data word

30 VX against one another for a prescribed relationship. Normally, this involves a comparison for identity between the applied third data word X3 and the first data word X1 as comparison data word VX. If the two data words to be checked are not identical or linked in

35 a defined manner, an alarm function ALARM is performed.

In the second transformation device R1, the data word

transformation corresponds to the second transformation T2. It is advantageously chosen such that this is a reverse function for the first transformation T1 provided by the first transformation device DEC. If no attack or transmission error has occurred, the third data word X3, which is present at the output of the second transformation device R1 and is passed to the checking device COMP, is identical to the first data word X1. In the case of data errors which are random or caused by manipulations, the first and third data words X1, X3 no longer have a prescribed relationship, since the errors within the context of the first and/or second transformations T1, T2 lead to subsequent errors or are caused by the attack during the transformation itself. Since the first and second transformations T1, T2 differ, it is difficult to make the attack such that both transformations are manipulated in coordinated fashion, that data alterations remain unnoticed or that their consequences are removed for the transformations. During an extended attack, for example using light, both transformations deliver different errors which are detected during the comparison.

Figure 5 differs from Figure 4 merely in that a third transformation device R2 is coupled between the first buffer 1 and the checking device COMP. The text below discusses only the differences.

Producing the hardware implementation of the reverse function in the second transformation device R1 is frequently a difficulty. In these cases, it is not possible to design the second transformation device R1 such that the original first data word X1 is present at its output again. In such cases, only a partial reverse transformation is performed in the second transformation device R1, the result of which is the third data word X3. The still outstanding portion of

first buffer 1 and the checking device COMP. For this,
the third transformation device R2 is provided. R2 is
designed such that it is used to produce the third
transformation T3. This means that ideally the same
5 data word is present at the output of the third
transformation device R2 as at the output of the second
transformation device R1. Alternatively, the data words
may also be in a different, prescribed relationship.
These data words are compared with one another in the
10 checking device COMP.

In the extreme case, the second transformation device
R1 may be in a very simple form or may be dispensed
with completely, so that the second buffer 2 would be
15 connected directly to the checking device COMP. This
corresponds to the identity as second transformation
T2. In such cases, the third transformation T3, which
is provided via the third transformation device R2, is
advantageously the same as the first transformation T1,
20 which is executed in the first transformation device
DEC. The same transformation is therefore executed on
two paths. This refinement of the circuit arrangement
has the drawback that it is naturally possible for an
identical attack to be made on two identically working
25 devices, which results in the same errors, so that
manipulation would remain undetected in the checking
device COMP. In the embodiments described above, two or
even three different transformation devices DEC, R1, R2
are provided on which different, coordinated attacks
30 would need to be made in order for these attacks to
remain undetected.

The first transformation device DEC and the second
transformation device R1 both in Figure 4 and in Figure
35 5 may advantageously be in a form such that the
resultant third data word X3 can be associated
distinctly or cannot be associated distinctly. The

converted into a sequence S2 of second data words X2 by the first transformation device DEC.

5 If the third data word X3 cannot be associated distinctly, that is to say that a plurality of possible first data words can be associated with the third data word X3, the checking device COMP establishes merely whether the association is conclusive. Alternatively, the first transformation device DEC, for example by 10 virtue of an internal device 3, is in a form such that information I is added to the second data word X2, so that the first data word X1 and the comparison data word VX, be it the first data word X1 or its transformed form X1', can be put into a distinct 15 relationship. In this case, the second transformation device R1 also delivers a third data word X3, which corresponds distinctly to the first data word X1 or to its transformed form X1' at the output of the third transformation device R2. It is also conceivable for 20 the information I to be provided by a separate device, coupled to or in parallel with the first transformation device DEC.

As regards the reaction of the circuit arrangement to 25 an alarm function ALARM which may need to be executed, it should be noted that these may be in a wide variety of forms. They depend both on the safety concept and on the architecture of the circuit arrangement. By way of example, it is conceivable for an alarm signal to be 30 output, for the circuit arrangement to be shut down, for the circuit arrangement to be shut down and started up again, or for the erroneous data word to be subjected to repeat data processing.

35 In addition, it should be noted that the inventive method is not just limited to conventional circuit arrangements for the actual data processing. It is also

device. In this case, a check is carried out to determine whether the requested data word has been manipulated in the course of the request and the upload.